

PUZZLE-7030A

1U Rackmount Network Appliance with Intel® Xeon® D Processor series (Code Name: Ice Lake-D LCC)



Features

- » Intel® Xeon® D Processor series (Code Name: Ice Lake-D LCC)
- » 4 x DDR4 2400M/2933Hz ECC UDIMM/RDIMM, up to 256G
- » 8 x 2.5 Gbps RJ-45 LAN ports & 5 x 10 Gbps SFP+ ports
- » 1 x FH PCIe Gen4 x8 or 2 x FH PCIe Gen4 x4 and 1 x OCP 3.0 slot
- » 1 x RJ-45 Console, 2 x USB 3.0, LCM
- » 2 x 2.5" SATA slot, 2 x M.2 M key 2280 (SATA/PCIe Gen3 x2), 1 x M.2 B key for IPMI module (support IEI iRIS2 IPMI module)
- » 320W Redundant Power Supply

Specifications

尺寸类型	
尺寸类型	1U
系统	
CPU	Intel® Xeon® D Processor series (Code Name: Ice Lake-D LCC)
芯片组	Integrated in CPU
内存	DDR4 2400M/2933Hz ECC UDIMM/RDIMM
内存上限	Up to 256G
散热方案/系统风扇	3x Cooling Fans with Smart Fan
	1 x System Fan
物理特性	
Rack Height	1U
尺寸 (LxWxH) (mm)	436.2 x 454.3 x 44.2
存储	
存储	2 x 2.5" SSD/HDD Bay : support SATA 3.0 (6 Gbps)
I/O 接口	
网络	5 x SFP+ : 10 GbE
	8 x LAN : 2.5 GbE RJ45 (Intel®KTI225V)
I/O接口	1 x Console port(s) : RJ45
	2 x USB 3.0
扩展	PCIe x8 : 1 x FH PCIe Gen4 x8 or 2 x FH PCIe Gen4 x4
	3 x M.2(NGFF) : 2 x M key 2280 (SATA/PCIe Gen3 x2) 1 x B key for IPMI module (support IEI iRIS2 IPMI module)
电源	
电源供电	320W Redundant Power Supply
环境	
操作温度	0°C ~ 40°C (32°F ~ 104°F)
存储温度	-10°C ~ 50°C
Humidity	5% ~ 90% non-condensing
认证	
Safety & EMC	By customer request
OS Support	
OS Support	Ubuntu, Linux based OS

Ordering Information

PUZZLE-7030A-R20	1U Rackmount Network Appliance with Intel Ice Lake-D LCC processor
------------------	--

Packing List

2 x Power cord	2 x Rack mounting ears
6 x Screw for 2.5-inch drives	