

AUPS2-A20

Gen2 Intelligent DC UPS Module



Features

- » 50W (4.17A@12V) output
- » 28Wh for more than 60 minutes operation time (depending on panel PC power requirements)
- » Rugged metal enclosure for Din-rail, standard VESA 75 and Wall mounting
- » Web-based, remote network management, no software installation required
- » Local PC-based monitoring software for input detection and battery status monitoring
- » Auto shut down when battery low
- » Remote DC output on/off switch for external switch installation
- » Provides stable power to the PC during line sags and spikes and absorbs power surges and transients, protecting expensive equipment

Specifications

Environment	
Operating Temperature	0°C ~ 40°C
Storage Temperature	-20°C ~ 50°C
Input	
Voltage	12-24V DC
Output	
Voltage	12V DC
General	
Watt	50W
Dimensions	151.7 x 101.35 x 29.2
Output Connector	1 x DC JACK (Input)
	1 x DC JACK (Output)
	1 x 2 Pin Terminal block
	1 x RJ45
	1 x USB2.0 Type-A
Weight	
Weight	0.75/1.2 kg

Ordering Information

AUPS2-A20-R10	VESA 75, DC 12~14V input 60W UPS module with 7.26V;5600mAH, 2S2P Li-Ion battery, R10
---------------	--

Packing List

1 x USB cable (USB Type-A to USB Type-A 915mm) (32001-006103-100-R5)	1 x Power cable (DC PLUG 5.5*2.5mm to DC PLUG 5.0*2.1mm, 150mm) (32002-004700-100-R5)
1 x Terminal block (2 Pin, P=3.5mm) (33502-000203-R5)	2 x Wall mouing kit
1 x DIN-Rail mounting kit	1 x Screw pack