

## RACK-2040

## 2U 7-slot ATX Rackmount Chassis



## Features

- » Compatible with ATX and microATX and Mini-ITX motherboards
- » Two USB ports on the front panel
- » Two 8 cm cooling fans
- » Two 3.5" and two 2.5" drive bays
- » RoHS compliant design

## Specifications

|                             |                                                          |
|-----------------------------|----------------------------------------------------------|
| Form factor                 |                                                          |
| SBC Form Factor             | ATX and microATX and Mini-ITX motherboards               |
| I/O Interface               |                                                          |
| I/O Ports                   | 2 x USB (Front panel)                                    |
| Expansion Slots             |                                                          |
| Expansion Slots             | 7 slots (Half-height size)                               |
| System                      |                                                          |
| Cooling method / System Fan | 2 x 80 mm Fan                                            |
| Drive Bays                  | 2 x 3.5" HDD bay                                         |
|                             | 2 x 2.5" HDD bay                                         |
| Indicator&Buttons           |                                                          |
| Buttons                     | Power switch, Reset button                               |
| Indicators                  | Power Led                                                |
| Physical Characteristics    |                                                          |
| Construction                | Heavy duty metal                                         |
| Color                       |                                                          |
| Color                       | Black                                                    |
| Dimensions                  |                                                          |
| Dimensions                  | 431.6 x 495 x 88 mm                                      |
| Weight                      |                                                          |
| Weight                      | 5.6kg / 9.6kg                                            |
| Environment                 |                                                          |
| Operating Temperature       | -10°C ~ 60°C                                             |
| Humidity                    | 10% ~ 90%                                                |
| Operating Vibration         | Half-sine wave shock 5G, 11ms, 100 shocks per axis (SSD) |
| Operating Shock             | MIL-STD-810F 514.5C-1 (SSD)                              |
| Safety & EMC                | CE/FCC compliant                                         |

## Ordering Information

|                  |                                                                                                                 |
|------------------|-----------------------------------------------------------------------------------------------------------------|
| RACK-2040-7S-R10 | 2U 7 Half-height slot ATX Rackmount Chassis, 2xUSB2.0, ATX Power Switch, 490mm depth, Powder paint, Black, RoHS |
|------------------|-----------------------------------------------------------------------------------------------------------------|

## Packing List

|                        |                    |
|------------------------|--------------------|
| 2 x Rack mounting ears | 1 x Mounting Screw |
| 1 x Power Cord         |                    |