

PAC-5011

MINI-ITX Compact Chassis



Features

- » Mini-ITX & IEI extended mini-ITX embedded chassis
- » Compatible with IEI proprietary extended mini-ITX SBC (depth +30 mm)
- » 2-slot PCI/PCIe half-height, half-length expansion
- » Supports 1U FLEX power supply
- » Up to 3 x 2.5" internal drive bays
- » RoHS compliant design

Specifications

Form factor	
SBC Form Factor	Mini-ITX & IEI extended mini-ITX
I/O Interface	
I/O Ports	2 x USB
Expansion Slots	
Expansion Slots	2 slots
System	
Drive Bays	3 x 2.5" HDD bay
Indicator&Buttons	
Buttons	Power switch, reset button
Indicators	Power LED
Physical Characteristics	
Construction	Heavy duty metal
Color	
Color	Gray
Dimensions	
Dimensions	270.20 x 267 x 88.6 (mm)
Weight	
Weight	2.1kg / 3.6kg
Environment	
Operating Temperature	-10°C ~ 50°C
Humidity	10% ~ 90%
Operating Vibration	Half-sine wave shock 5G, 11ms, 100 shocks per axis (SSD)
Operating Shock	MIL-STD-810F 514.5C-1 (SSD)
Safety & EMC	CE/FCC compliant

Ordering Information

PAC-5011-R10	Extended-ITX two Half-height slot ATX Chassis,2xUSB2.0,ATX Power Switch,Gray,Powder paint,RoHS
--------------	--

Packing List

2 x Wall Mount Bracket	1 x Mounting Screw
------------------------	--------------------