

# 63030-010180-000-RS

## 1U flex ATX 180W Power Supply



### Features

1U flex ATX 180W Power Supply

### Specifications

| Input                    |   |
|--------------------------|---|
| Voltage                  | 90~264 VAC Full Range                           |
| Frequency                | 47 Hz ~ 63 Hz                                   |
| Input Current            | 3A (RMS)@115VAC, 1.5A (RMS)@230VAC              |
| Inrush Current           | 80A max. for 115VAC, 160A max. for 230VAC       |
| Output                   |   |
| Voltage                  | +3.3V/10A,+5V/14A,+12V/10A,-12V/0.3A,+5Vsb/2.5A |
| Over Voltage Protection  | +3.3V: 3.7V-4.8V                                |
|                          | +5V: 5.55V-7.0V                                 |
|                          | +12V1 : 13.3V-16V                               |
| Short Circuit Protection | +3.3V, +5V, +12V, -12V shutdown and latch off   |
| General                  |   |
| Watt                     | 180   |
| Efficiency               | 85%   |
| MTBF                     | 100000  |
| Operating temperature    | 0°C ~ 50°C                                      |
| Storage temperature      | -20°C ~ 80°C                                    |
| Dimensions               | 150 x 81.5 x 40.5                               |
| Output Connector         | 1 x 20+4-PIN ATX,                               |
|                          | 1 x 4-pin 12V CPU,                              |
|                          | 1 x HDD/CDROM,                                  |
|                          | 1 x FDD,  |
|                          | 2 x SATA  |

### Ordering Information

|                     |  |
|---------------------|--|
| 63030-010180-000-RS | FLEX;FSP;FSP180-50FBB;9PA1806108;Active<br>PFC;Vin:90~264VAC;180W;150*81.5*40.5mm;;;80Plus(SILVER);Vout:ATX;ATX;CCL;RoHS |
|---------------------|--|