

# iUCOM-2D

USB Module supports two RS-232/422/485 Port (DB-9), RoHs



## Features

- » Two-ports RS-232/422/485 (DB-9)
- » 1024 bytes transmit/ 512 bytes receive FIFO
- » High-speed 16C550/16C650/16C750/16C850 compatible UARTs
- » Baud rate supports 115.2K, max. up to 6M

## Specifications

Form Factor	
Form Factor	USB2.0 (1*4pin, P=2.0)
	* USB Bridge to Quad Serial Port: WCH CH342
	* Buffer/Transceiver Series: F81435
Physical Characteristics	
Dimensions (LxWxH) (mm)	65mm * 35mm
I/O Interface	
I/O Interface	2 x External RS-232/422/485 : DB-9
Environment	
Operating Temperature	0°C – 60°C
Storage Temperature	-30°C –70°C
Humidity	5% ~ 95%, non-condensing
Certifications	
Safety & EMC	CE/FCC compliant

## Ordering Information

iUCOM-2D-R10	USB Module supports two RS-232/422/485 Port(DB9), RoHs
--------------	--------------------------------------------------------

## Packing List

1 x iUCOM-2D peripheral board	1 x QIG
1 x USB Cable(P=2.0)	1 x USB Cable(P=2.54)