

# PAC-5011

## MINI-ITX Compact Chassis



## Features

- » Mini-ITX & IEI extended mini-ITX embedded chassis
- » Compatible with IEI proprietary extended mini-ITX SBC (depth +30 mm)
- » 2-slot PCI/PCIe half-height, half-length expansion
- » Supports 1U FLEX power supply
- » Up to 3 x 2.5" internal drive bays
- » RoHS compliant design

## Specifications

|                          |                                                          |
|--------------------------|----------------------------------------------------------|
| Form factor              |                                                          |
| SBC Form Factor          | Mini-ITX & IEI extended mini-ITX                         |
| I/O Interface            |                                                          |
| I/O Ports                | 2 x USB                                                  |
| Expansion Slots          |                                                          |
| Expansion Slots          | 2 slots                                                  |
| System                   |                                                          |
| Drive Bays               | 3 x 2.5" HDD bay                                         |
| Indicator&Buttons        |                                                          |
| Buttons                  | Power switch, reset button                               |
| Indicators               | Power LED                                                |
| Physical Characteristics |                                                          |
| Construction             | Heavy duty metal                                         |
| Color                    |                                                          |
| Color                    | Gray                                                     |
| Dimensions               |                                                          |
| Dimensions               | 270.20 x 267 x 88.6 (mm)                                 |
| Weight                   |                                                          |
| Weight                   | 2.1kg / 3.6kg                                            |
| Environment              |                                                          |
| Operating Temperature    | -10°C ~ 50°C                                             |
| Humidity                 | 10% ~ 90%                                                |
| Operating Vibration      | Half-sine wave shock 5G, 11ms, 100 shocks per axis (SSD) |
| Operating Shock          | MIL-STD-810F 514.5C-1 (SSD)                              |
| Safety & EMC             | CE/FCC compliant                                         |

## Ordering Information

|              |                                                                                                |
|--------------|------------------------------------------------------------------------------------------------|
| PAC-5011-R10 | Extended-ITX two Half-height slot ATX Chassis,2xUSB2.0,ATX Power Switch,Gray,Powder paint,RoHS |
|--------------|------------------------------------------------------------------------------------------------|

## Packing List

|                        |                    |
|------------------------|--------------------|
| 2 x Wall Mount Bracket | 1 x Mounting Screw |
|------------------------|--------------------|