

BRICK-KINO

IEI DC 输入 Mini-ITX SBC 嵌入式机箱

Features

- » 专为 Mini-ITX SBCs 而设计，具有 DC 输入
- » 灵活的 SBC 兼容性
- » 一个 2.5" 硬盘容量
- » 经济高效，符合 RoHS 标准的设计



BRICK Chassis with eKINO-BT (SBC not included)

Specifications

外形尺寸	
SBC 外形	Refer to KINO Series
I/O 接口	
I/O 开孔	Reserved IO window for COM port expansion
I/O 端口	Refer to SBCs
扩展槽	
扩展槽	Refer to SBCs
系统	
散热方式 / 系统风扇	Refer to SBCs
驱动器托架	1 x 2.5" HDD bay
指示器和按钮	
按钮	Power switch with LED
颜色	
颜色	Black
尺寸	
尺寸	203 x 178 x 64 mm
重量	
重量	1.25kg/1.5kg
运行环境	
操作温度	0°C ~ 40°C

Ordering Information

BRICK-tKINO-ULT3-R10	Embedded chassis for tKINO-ULT3 SBC, with IO bracket ,power switch, mat black and RoHS
BRICK-tKINO-BW-R10	Embedded chassis for tKINO-BW SBC, with IO bracket ,power switch, mat black and RoHS
BRICK-tKINO-AL-R10	Embedded chassis for tKINO-AL SBC, with IO bracket ,power switch, mat black and RoHS
BRICK-eKINO-BT-R10	Embedded chassis for eKINO-BT SBC, with IO bracket ,power switch, mat black and RoHS
BRICK-KINO-DBT-R10	Embedded chassis for KINO-DBT SBC, with IO bracket ,power switch, mat black and RoHS

BRICK-KINO-DAL-R10

Embedded chassis for KINO-DAL SBC, with IO bracket ,power switch, mat black and RoHS

Packing List

1 x BRICK 机箱	1 x 电源开关线
1 x 螺丝组	1 x QIG