

## BRICK-NANO

IEI DC 输入 EPIC/3.5" SBC 嵌入式机箱

## Features

- » 专为 EPIC / 3.5" SBC 设计，具有 DC 输入
- » 灵活的 SBC 兼容性
- » 一个 2.5" 硬盘容量
- » 经济高效，符合 RoHS 标准的设计



BRICK Chassis with WAFER-AL (SBC not included)

## Specifications

| 外形尺寸        |                                           |
|-------------|-------------------------------------------|
| SBC 外形      | Refer to NANO/WAFER Series                |
| I/O 接口      |                                           |
| I/O 开孔      | Reserved IO window for COM port expansion |
| I/O 端口      | Refer to SBCs                             |
| 扩展槽         |                                           |
| 扩展槽         | Refer to SBCs                             |
| 系统          |                                           |
| 散热方式 / 系统风扇 | Refer to SBCs                             |
| 驱动器托架       | 1 x 2.5" HDD bay                          |
| 指示器和按钮      |                                           |
| 按钮          | Power switch with LED                     |
| 颜色          |                                           |
| 颜色          | Black                                     |
| 尺寸          |                                           |
| 尺寸          | 220 x 143 x 55 mm                         |
| 重量          |                                           |
| 重量          | 1.2kg/1.5kg                               |
| 运行环境        |                                           |
| 操作温度        | 0°C ~ 40°C                                |

## Ordering Information

|                    |                                                                                                                  |
|--------------------|------------------------------------------------------------------------------------------------------------------|
| BRICK-WAFER-BT-R10 | Embedded chassis for WAFER-BT SBC, with SATA cable, IO bracket ,power switch, DC input cable, mat black and RoHS |
| BRICK-WAFER-AL-R10 | Embedded chassis for WAFER-AL SBC, with SATA cable, IO bracket ,power switch, DC input cable, mat black and RoHS |
| BRICK-NANO-BT-R10  | Embedded chassis for NANO-BT SBC, with SATA cable, IO bracket ,power switch, DC input cable, mat black and RoHS  |

BRICK-NANO-AL-R10

Embedded chassis for NANO-AL SBC, with SATA cable, IO bracket ,power switch, DC input cable, mat black and RoHS

## Packing List

|              |           |
|--------------|-----------|
| 1 x BRICK 机箱 | 1 x 电源开关线 |
| 1 x 螺丝组      | 1 x QIG   |
| 1 x SATA 线   |           |