

AUPS2-A20

Gen2 Intelligent DC UPS Module



Features

- » 50W (4.17A@12V) output
- » 28Wh for more than 60 minutes operation time (depending on panel PC power requirements)
- » Rugged metal enclosure for Din-rail, standard VESA 75 and Wall mounting
- » Web-based, remote network management, no software installation required
- » Local PC-based monitoring software for input detection and battery status monitoring
- » Auto shut down when battery low
- » Remote DC output on/off switch for external switch installation
- » Provides stable power to the PC during line sags and spikes and absorbs power surges and transients, protecting expensive equipment

Specifications

| | |
|-----------------------|--------------------------|
| Environment | |
| Operating Temperature | 0°C ~ 40°C |
| Storage Temperature | -20°C ~ 50°C |
| Input | |
| Voltage | 12-24V DC |
| Output | |
| Voltage | 12V DC |
| General | |
| Watt | 50W |
| Dimensions | 151.7 x 101.35 x 29.2 |
| Output Connector | 1 x DC JACK (Input) |
| | 1 x DC JACK (Output) |
| | 1 x 2 Pin Terminal block |
| | 1 x RJ45 |
| | 1 x USB2.0 Type-A |
| Weight | |
| Weight | 0.75/1.2 kg |

Ordering Information

| | |
|---------------|--|
| AUPS2-A20-R10 | VESA 75, DC 12~14V input 60W UPS module with 7.26V;5600mAH, 2S2P Li-Ion battery, R10 |
|---------------|--|

Packing List

| | |
|--|---|
| 1 x USB cable (USB Type-A to USB Type-A 915mm) (32001-006103-100-RS) | 1 x Power cable (DC PLUG 5.5*2.5mm to DC PLUG 5.0*2.1mm, 150mm) (32002-004700-100-RS) |
| 1 x Terminal block (2 Pin, P=3.5mm) (33502-000203-RS) | 2 x Wall mouing kit |
| 1 x DIN-Rail mounting kit | 1 x Screw pack |