

PAC-5011

MINI-ITX Compact Chassis



Features

- » Mini-ITX & IEI extended mini-ITX embedded chassis
- » Compatible with IEI proprietary extended mini-ITX SBC (depth +30 mm)
- » 2-slot PCI/PCIe half-height, half-length expansion
- » Supports 1U FLEX power supply
- » Up to 3 x 2.5" internal drive bays
- » RoHS compliant design

Specifications

| | |
|--------------------------|--|
| Form factor | |
| SBC Form Factor | Mini-ITX & IEI extended mini-ITX |
| I/O Interface | |
| I/O Ports | 2 x USB |
| Expansion Slots | |
| Expansion Slots | 2 slots |
| System | |
| Drive Bays | 3 x 2.5" HDD bay |
| Indicator&Buttons | |
| Buttons | Power switch, reset button |
| Indicators | Power LED |
| Physical Characteristics | |
| Construction | Heavy duty metal |
| Color | |
| Color | Gray |
| Dimensions | |
| Dimensions | 270.20 x 267 x 88.6 (mm) |
| Weight | |
| Weight | 2.1kg / 3.6kg |
| Environment | |
| Operating Temperature | -10°C ~ 50°C |
| Humidity | 10% ~ 90% |
| Operating Vibration | Half-sine wave shock 5G, 11ms, 100 shocks per axis (SSD) |
| Operating Shock | MIL-STD-810F 514.5C-1 (SSD) |
| Safety & EMC | CE/FCC compliant |

Ordering Information

| | |
|--------------|--|
| PAC-5011-R10 | Extended-ITX two Half-height slot ATX Chassis,2xUSB2.0,ATX Power Switch,Gray,Powder paint,RoHS |
|--------------|--|

Packing List

| | |
|------------------------|--------------------|
| 2 x Wall Mount Bracket | 1 x Mounting Screw |
|------------------------|--------------------|