

iEi		
	PUZZLE-8010	PUZZLE-9070
Form Factor	2U rackmount	4U
CPU	Intel® Xeon® 600 Processors for Workstation (Code Name: Granite Rapids-WS)	Intel Xeon® 6 (Granite Rapids-SP)
Chipset	DDR5 6400 MT/s RDIMM	Integrated in CPU
Memory	Based on DIMM capacity	16 x DDR5 6400 MT/s RDIMM
Memory Max.	Based on DIMM capacity	Based on DIMM capacity
Cooling method / System Fan	3 x System fans	9 x System fans
Rack Height	2U	4U
Dimensions (LxWxH) (mm)	587 x 438 x 88	791 x 438 x 176.6
Net Weight	22 Kgs	25 kgs
Storage	2 x 2.5" SSD/HDD Bay: support PCIe Gen4 x4	2 x 2.5" SSD/HDD Bay(PCIe Gen 5 x16)
Ethernet	2 x SFP+: 10GbE SPF+ LAN ports 2 x LAN: 1GbE RJ45 LAN ports	2 x SFP+: 10GbE SPF+ LAN ports 2 x LAN: 1GbE RJ45 LAN ports
I/O Interface	2 x Console port(s): RJ45 ports/ USB type C 2 x USB 3.0: Type-A	2 x Console port(s): RJ45 port/ USB type C 2 x USB 3.0(Type-A)
Expansion	2 x PCIe x16: PCIe Gen5 x 16 FHFL 2 x M.2(NGFF): 2280 M Key	4 x PCIe x16: PCIe Gen5 x 16 FHFL 2 x M.2(NGFF): 2280 M Key
IPMI	1 x M.2 B Key Socket support IEI iRIS2 IPMI module 1 x 1 GbE RJ45 for IPMI port	1 x M.2 B Key Socket support IEI iRIS2 IPMI module 1 x 1 GbE RJ45 for IPMI port
TPM	1 x TPM 2.0 pin header	1 x TPM 2.0 pin header
Power Supply	2000W CRPS Redundant Power	4 x 2000W CRPS Redundant Power
Operating Temperature	0°C ~ 40°C (32°F ~ 104°F)	0°C ~ 40°C (32°F ~ 104°F)
Storage Temperature	-10°C ~ 50°C	-10°C ~ 50°C
Humidity	5% ~ 90% non-condensing	5% ~ 90% non-condensing
Safety & EMC	By customer request	By customer request
OS Compatible	Ubuntu, Linux based OS	Ubuntu, Linux based OS

