



	10-point multi-touch	10-point multi-touch
IP Level	Front: IP65, Back: IP32	Front: IP65, Back: IP32
Camera	5-megapixel CMOS front-facing camera with auto-focus and digital microphone	5-megapixel CMOS front-facing camera with auto-focus and digital microphone
System Cooling	Fanless	Fanless
Construction Front Panel	ABS+PC plastic with anti-bacterial material	ABS+PC plastic with anti-bacterial material
RAM	Two 260-pin 2400/2133MHz dual-channel DDR4 SO-DIMM, 4GB pre-installed (system max. 32GB)	Two 260-pin 2400/2133MHz dual-channel DDR4 SO-DIMM, 4GB pre-installed (system max. 32GB)
Microphone	digital microphone	digital microphone
I/O Ports and Switches	2 x USB 2.0 (side) 4 x USB 3.0 port 2 x HDMI output 2 x GbE LAN port 2 x RS-232/422/485 1 x Audio out (side) + 1 x Mic in (side) 1 x Digital Mic 1 x DC jack	2 x USB 2.0 (side) 4 x USB 3.0 port 2 x HDMI output 2 x GbE LAN port 2 x RS-232/422/485 1 x Audio out (side) + 1 x Mic in (side) 1 x Digital Mic 1 x DC jack
OSD Function	1 x Brightness up 1 x Brightness down 1 x Volume up 1 x Volume down 1 x Touch lock & LCD on/off 1 x Task Manager & Power on/off	1 x Brightness up 1 x Brightness down 1 x Volume up 1 x Volume down 1 x Touch lock & LCD on/off 1 x Task Manager & Power on/off
LED Function	1 x RFID indicator 3 x Battery indicator (Color : Blue/Red) 1 x Power Indicator	1 x RFID indicator 3 x Battery indicator (Color : Blue/Red) 1 x Power Indicator
I/O Interface	1 x AT/ATX Switch 1 x Mic 1 x Line out 2 x USB 2.0 4 x USB 3.2 Gen1x1 2 x LAN(GbE) 2 x RS-232 2 x HDMI 1 x Power In(19V DC jack) 2 x Speaker	1 x AT/ATX Switch 1 x Mic 1 x Line out 2 x USB 2.0 4 x USB 3.2 Gen1x1 2 x LAN(GbE) 2 x RS-232 2 x HDMI 1 x Power In(19V DC jack) 2 x Speaker