

# DRPC-W-EHL

Fanless DIN-Rail Embedded System  
 Elkhart Lake Intel® Celeron™ Solution (up to 4 cores)



## Features

- » Supported CPU: Intel® Celeron™ J6412 2.0 GHz (up to 2.6 GHz, quad-core, TDP 10W)
- » Support dual independent display
- » 2 x 2.5GbE ports
- » 1 x M.2 A Key
- » 1 x M.2 B Key (with SIM card slot)
- » CE/FCC compliant

## Specifications

Form factor	
SBC Form Factor	» Supported CPU: Intel® Celeron™ J6412 2.0 GHz (up to 2.6 GHz, quad-core, TDP 10W)
	» Chipset: SoC
	» System Memory: Onboard LPDDR4X 3200MHz 8G (up to 16GB)
	» Power: DC Jack: 12 V DC
	» Consumption: 12V@2.5A (Intel J6412 With 4GB DDR4 Memory)
I/O Interface	
I/O Ports	» USB: 2 x USB 3.2 Gen 2
	» Ethernet: 2 x 2.5 GbE by Intel® I225V (colay I225LM)
	» Display: 1 x HDMI™ 1 x DP
	» TPM: Support Intel PTT
	» Watchdog Timer: Programmable 1 ~ 255 sec/min
Expansion Slots	
Expansion Slots	» M.2: 1 x M.2 A Key 2230 for WIFI & BT (optional) 1 x M.2 B Key (PCIe x2) 3042 w/SIM slot for 5G (optional)
System	
Cooling method / System Fan	Fanless 4-pin external system fan connector
Drive Bays	1 x 2.5" SATA 6Gb/s HDD/SSD bay
Indicator&Buttons	

Buttons	1 x Power button
	1 x Reset button
Indicators	1 x Power LED
	1 x HDD LED
<b>Physical Characteristics</b>	
Construction	Extruded aluminum alloy
<b>Color</b>	
Color	Black
<b>Dimensions</b>	
Dimensions	176 x 116 x 60.8 (mm)
<b>Weight</b>	
Weight	0.92/1.16 Kg
<b>Environment</b>	
Operating Temperature	-20°C ~ 60°C with air flow
Humidity	10% ~ 95% non-condensing
Operating Vibration	10-500 Hz, 1.04 Grms, random, 1 hr/axis
Operating Shock	Half-sine wave shock 5G, 11ms, 100 shocks per axis
Safety & EMC	CE/FCC compliant
<b>OS Support</b>	
OS Support	Microsoft Windows 10 / Windows 11, Linux

## Ordering Information

DRPC-W-EHL-JC-R10	Fanless System with Intel® Celeron® J6412 up to 2.6GHz TDP 10W, 2 x 2.5GbE Lan, 1 x HDMI™, 1 x DP, 1 x 2.5" SATA HDD bay, 8GB memory pre-installed, 12V DC, RoHS
-------------------	--

## Packing List

1 x DIN-rail mounting kit	1 x Screw pack
1 x SATA cable with power cable	