

AURA-W185-RK3576

IEI's New generation industrial Panel PC



Features

- » IP65-rated front panel with robust aluminum bezel for harsh industrial environments
- » Flat-bezel PCAP touch with anti-glare / anti-UV coating for clear visibility in bright areas
- » Rockchip RK3576 octa-core SoC with 6 TOPS NPU for edge AI acceleration
- » Front-panel hard keys (hotkeys) for quick access to essential controls
- » PCAP touch with glove-friendly operation
- » Front-facing speakers & integrated camera options, ideal for HMI and vision-assisted applications
- » Rich I/O & wide-range power input (10–28V DC) for industrial integration

Specifications

System	
CPU	Rockchip RK3576 (Quad Cortex-A72 and quad Cortex-A53, 6 TOPS NPU)
On-board Memory	Onboard 8GB LPDDR5 memory, up to 16GB
Storage	Onboard 64GB eMMC
	1 x SD Slot
I/O Interface	
Ethernet	2 x RJ45 By YT8531
Audio	1 x Mic in & Line out
	2 x internal 2W speaker
Expansion	1 x board to board connector (Only supports IEI wireless modules)
	1 x 3042/52/80 B-key (PCIe Gen2 x1, USB2.0)
	1 x On-board SIM card socket (hinge type) for M.2 B key
I/O Ports	2 x RS232 & 2 x 485 By 1 x DB9
	1 x USB Type-C (USB 3.2 Gen1 + Displayport Alt Mode)
	3 x USB 2.0 Type-A
	1 x USB 3.2 Gen1 Type-A
	2 x CAN2.0 (6-pin terminal block)
	1 x Power button
	1 x Reset button
	1 x System LED (Orange)
Power	
Input	1 x 2-pin terminal block (10-28V DC)
Power consumption	12V@2.25A (Rockchip® RK3576 with 8GB Memory, 64G eMMC, Debian OS)
Environment	
Operating Temperature	-10°C ~ 60°C
Operating Vibration	MIL-STD-810H 514.8C-I with SSD
Operating Shock	IEC60068-2-27 half-sine, 5G, 11ms, 100 shocks with SSD
Safety & EMC	CE/FCC
Humidity	10% to 95%@40°C (non-condensing) (50%@60°C)
Storage Temperature	-20°C ~ 70°C
IP Level	IP 65 compliant front panel
Physical Characteristics	

Color	Black
Mounting	Panel Mount, Rack Mount, VESA 100
Dimensions (LxWxH) (mm)	458.40 x 288.80 x 51.20
Net Weight	4.73kg / 7.2kg
Construction	Aluminum front frame and sheet metal rear cover
Cutout Dimensions	440 x 264
LCD	
Size	18.5" (16:9)
Resolution	1920 x 1080
Brightness (cd/m2)	350
Contrast Ratio	1200:1
LCD Color	16.7M
Viewing Angle (H-V)	170° / 170°
Backlight MTBF	50000 hrs
Touch	
Touch Screen	PCAP with USB interface (anti-UV/AG coating)
Touch Controller	Capacitive: Litek
Other Features	
Camera	720P Wide Angle Fixed Focus
Function Key	
Function Key	5-key Hot Key
OS Compatible	
OS Compatible	Android / Debian

Ordering Information

AURA-W185-RK3576-CFD-R10	18.5" 350 cd/m ² 1920x1080 Panel PC with Rockchip RK3576, 8GB LPDDR5, 64GB eMMC, 2xRJ45, CAN, COM, USB Type-C, black, 10-28V DC input, PCAP touch, Debian 12, R10
AURA-W185-RK3576-CFA-R10	18.5" 350 cd/m ² 1920x1080 Panel PC with Rockchip RK3576, 8GB LPDDR5, 64GB eMMC, 2xRJ45, CAN, COM, USB Type-C, black, 10-28V DC input, PCAP touch, Android 14, R10

Packing List

11 x Panel Mount Kit	1 x Terminal block plugs (1x2pin)
1 x Terminal block plugs (2x3pin)	1 x Screw kit (for installation)