

# AURA-W238-RK3576

IEI's New generation industrial Panel PC



## Features

- » IP65-rated front panel with robust aluminum bezel for harsh industrial environments
- » Flat-bezel PCAP touch with anti-glare / anti-UV coating for clear visibility in bright areas
- » Rockchip RK3576 octa-core SoC with 6 TOPS NPU for edge AI acceleration
- » Front-panel hard keys (hotkeys) for quick access to essential controls
- » PCAP touch with glove-friendly operation
- » Front-facing speakers & integrated camera options, ideal for HMI and vision-assisted applications
- » Rich I/O & wide-range power input (10–28V DC) for industrial integration

## Specifications

<b>System</b>	
CPU	Rockchip RK3576 (Quad Cortex-A72 and quad Cortex-A53, 6 TOPS NPU)
On-board Memory	Onboard 8GB LPDDR5 memory, up to 16GB
Storage	Onboard 64GB eMMC
	1 x SD Slot
<b>I/O Interface</b>	
Ethernet	2 x RJ45 By YT8531
Audio	1 x Mic in & Line out
	2 x internal 2W speaker
Expansion	1 x board to board connector (Only supports IEI wireless modules)
	1 x 3042/52/80 B-key (PCIe Gen2 x1,USB2.0)
	1 x On-board SIM card socket (hinge type) for M.2 B key
I/O Ports	2 x RS232 & 2 x 485 By 1 x DB9
	1 x USB Type-C (USB 3.2 Gen1 + Displayport Alt Mode )
	3 x USB 2.0 Type-A
	1 x USB 3.2 Gen1 Type-A
	2 x CAN2.0 (6-pin terminal block)
	1 x Power button
	1 x Reset button
	1 x System LED (Orange)
<b>Power</b>	
Input	1 x 2-pin terminal block (10-28V DC)
Power consumption	12V@2.1A (Rockchip® RK3576 with 8GB Memory, 64G eMMC, Debian OS)
<b>Environment</b>	
Operating Temperature	10°C ~ 50°C
Operating Vibration	MIL-STD-810H 514.8C-I with SSD
Operating Shock	IEC60068-2-27 half-sine, 5G, 11ms, 100 shocks with SSD
Safety & EMC	CE/FCC
Humidity	10% to 95%@40°C (non-condensing) ( 50%@60°C )
Storage Temperature	-20°C ~ 60°C
IP Level	IP 65 compliant front panel
<b>Physical Characteristics</b>	

Color	Black
Mounting	Panel Mount, Rack Mount, VESA 100
Dimensions (LxWxH) (mm)	571.4 x 354.50 x 51.20
Net Weight	6.65kg / 9.4kg
Construction	Aluminum front frame and sheet metal rear cover
Cutout Dimensions	553 x 330
<b>LCD</b>	
Size	23.8" (16:9)
Resolution	1920 x 1080
Brightness (cd/m2)	350
Contrast Ratio	1000:1
LCD Color	16.7M
Viewing Angle (H-V)	178° / 178°
Backlight MTBF	30000 hrs
<b>Touch</b>	
Touch Screen	PCAP with USB interface (anti-UV/AG coating)
Touch Controller	Capacitive: Litek
<b>Other Features</b>	
Camera	720P Wide Angle Fixed Focus
<b>Function Key</b>	
Function Key	5-key Hot Key
<b>OS Compatible</b>	
OS Compatible	Android / Debian

## Ordering Information

AURA-W238-RK3576-CFD-R10	23.8" 350 cd/m <sup>2</sup> 1920x1080 Panel PC with Rockchip RK3576, 8GB LPDDR5, 64GB eMMC, 2xRJ45, CAN, COM, USB Type-C, black, 10-28V DC input, PCAP touch, Debian 12, R10
AURA-W238-RK3576-CFA-R10	23.8" 350 cd/m <sup>2</sup> 1920x1080 Panel PC with Rockchip RK3576, 8GB LPDDR5, 64GB eMMC, 2xRJ45, CAN, COM, USB Type-C, black, 10-28V DC input, PCAP touch, Android 14, R10

## Packing List

12 x Panel Mount Kit	1 x Terminal block plugs (1x2pin)
1 x Terminal block plugs (2x3pin)	1 x Screw kit (for installation)