

ACE-A160B

600 W PS/2 ATX Power Supply with ErP



Features

600 W PS/2 ATX Power Supply with ErP

Specifications

| Input | |
|--------------------------|---|
| Voltage | 90~264 VAC Full Range |
| Frequency | 47 Hz ~ 63 Hz |
| Input Current | 8A (RMS)@115VAC, 4A (RMS)@230VAC |
| Inrush Current | 40A max. for 115VAC, 80A max. for 230VAC |
| Output | |
| Voltage | +3.3V/25A,+5V/25A,+12V1/16A,+12V2/16A,+12V3/16A,+12V4/16A,-12V/0.5A,+5Vsb/4A,-5V/0.5A |
| Over Voltage Protection | +3.3V: 3.9V-4.5V |
| | +5V: 5.7V-6.5V |
| | +12V1 ~ +12V4: 13.3V-16.7V |
| Short Circuit Protection | +3.3V, +5V, +12V1, +12V2, +12V3, +12V4, 24V or -12V shutdown and latch off |
| General | |
| Watt | 600 |
| Efficiency | 82% |
| MTBF | 100000 |
| Operating temperature | 0°C ~ 50°C |
| Storage temperature | -20°C ~ 80°C |
| Dimensions | 140 x 150 x 86 |
| Output Connector | 1 x 20+4-pin ATX, |
| | 2 x 4-pin 12V CPU, |
| | 9 x HDD/CDROM, |
| | 1 x Graphics card power, |
| | 2 x FDD,2 x SATA |

Ordering Information

| | |
|---------------|--|
| ACE-A160B-R11 | 600W PS/2 ATX Power Supply with ERP;RoHS |
|---------------|--|