

AFL3P-W10MSR-U

Magnetic card reader with mounting bracket



Features

- » Magnetic card reader with mounting bracket
- » Scan Rate: 100-1000mm/sec
- » Magnetic Card: IISO 7810-7813 and JISII
- » Tracks T1&T2&T3: Decording Density T1/T2/T3: 210/75/210 BPI Capacity T1/T2/T3: 79/40/107 Characters
- » Life Cycle: 300,000 passes

Specifications

| | |
|-----------------------|---|
| Environment | |
| Operating Temperature | 0°C ~ 50°C |
| Storage Temperature | -20°C ~ 70°C |
| Input | |
| Voltage | 5V DC USB |
| General | |
| MTBF | 24,000 hours |
| Dimensions | 90.0mm X 29.00mm X 38.00mm |
| Material | |
| Material | Plastic |
| Weight | |
| Weight | 61.2 g (net weight) |
| Key Features | |
| Key Features | Magnetic card reader with mounting bracket |
| | Scan Rate: 100-1000mm/sec |
| | Magnetic Card: IISO 7810-7813 and JISII |
| | Tracks T1&T2&T3: Decording Density T1/T2/T3: 210/75/210 BPI Capacity T1/T2/T3: 79/40/107 Characters |
| | Life Cycle: 300,000 passes |

Ordering Information

| | |
|--------------------|---|
| AFL3P-W10MSR-U-R10 | Magnetic card reader with USB interface, for AFL3-08A-BT/AFL3-W10A-BT/AFL3-12A-BT/AFL3-W15A-BT/AFL3-W15B-H81, R10 |
|--------------------|---|