


PCIe-Q370

Full-size PICMG 1.3 CPU Card supports LGA1151 Intel® Core™ i9/i7/i5/i3/ Pentium®/Celeron® CPU per Intel® Q370, DDR4, VGA/HDMI™ and DP, Dual Intel® PCIe GbE, USB 3.1, SATA 6Gb/s, M.2, HD Audio, iAMT and RoHS



Features

- » PICMG 1.3 full-size CPU card
- » LGA1151 Intel® 8th/9th Generation Core™ i9/i7/i5/i3, Celeron® and Pentium® processor supported
- » Dual-channel DDR4 2666MHz
- » Support VGA/HDMI™ and Internal DP displays
- » Intel® PCIe GbE with Intel® AMT 11.0 supported
- » Support M.2 M key for storage (PCIe x4)
- » Supports RAID 0, 1, 5, 10 function via SATA 6Gb/s

Specifications

| System | |
|--------------------------|--|
| CPU | LGA1151 socket supports 8th/9th generation Intel® Core™ i9/i7/i5/i3, Pentium® or Celeron® processor |
| Chipset | Intel® Q370 |
| Memory | Four 288-pin 2666MHz dual-channel DDR4 SDRAM unbuffered DIMMs |
| Memory Max. | 64GB |
| Physical Characteristics | |
| Dimensions (LxWxH) (mm) | 338 X 126 |
| Net Weight | 500g |
| Storage | |
| Storage | 6 x SATA :6Gb/s (RAID 0/1/5/10 supported) |
| I/O Interface | |
| Display Output | 1 x HDMI™ :up to 1920x1080@60Hz; up to 4096x2304@30Hz(PCIe-Q370-HDMI™-R11); 1 x Display Port :up to 4096x2304@60Hz,Internal |
| Ethernet | 2 x LAN :LAN1: Intel® I219LM PHY LAN2: Intel® I211-AT PCIe controller (Co-lay I210-AT) |
| Audio | Description: Support 7.1 channel HD Audio by IEI AC-KIT-892HD kit |
| I/O Interface | 3 x Internal RS-232 :2x5 pin, P=2.54 1 x Internal RS-422/485 :1x4 pin, p=2.0 1 x External USB 2.0 :5Gb/s(Rear I/O type A) 2 x External USB 3.2 Gen1x1 6 x Internal USB 2.0 :2x4 pin, p=2.54 1 x Internal USB 3.2 Gen1x1 :2x10 pin,5Gbs 1 x PS/2 :1x6 pin |
| Expansion | 1 x PCIe x16 :signal via golden finger |

| | |
|-----------------------|--|
| | 4 x PCIe x1 :signal via golden finger |
| | 4 x PCI Slot :PCI signal via golden finger |
| | 1 x M.2(NGFF) :2280,Gen 3 PCIe X 4 |
| Other Features | |
| TPM | 2x10 pin |
| Power | |
| Power Consumption | 5V@3.12A, 12V@6.85A, 3.3V@1.13A, 5VSB@0.15A (4.0 GHz Intel® Core™ i7-8700K CPU with four 16 GB 2666 MHz DDR4 memory) |
| Power Supply | Support AT/ATX mode |
| Environment | |
| Operating Temperature | -20°C ~ 60°C |
| Humidity | 5% ~ 95%, non-condensing |
| Certifications | |
| Safety & EMC | CE/FCC compliant |

Ordering Information

| | |
|---------------|--|
| PCIE-Q370-R11 | Full-size PICMG 1.3 CPU Card supports LGA1151 Intel® Core™ i9/i7/i5/i3/Pentium®/Celeron® CPU per Intel® Q370, DDR4, VGA, DP, Dual Intel® PCIe GbE, USB 3.2, SATA 6Gb/s, M.2, HD Audio, iAMT and RoHS |
|---------------|--|

Packing List

| | |
|-------------------------------------|------------------------------------|
| 1 x PCIE-Q370 single board computer | 1 x SATA cable |
| 1 x Mini jumper pack | 1 x QIG (Quick Installation Guide) |