

ACE-A630C

1U flex ATX 300W Power Supply



Features

1U flex ATX 300W Power Supply

Specifications

| Input | |
|--------------------------|---|
| Voltage | 90~264 VAC Full Range |
| Frequency | 47 Hz ~ 63 Hz |
| Input Current | 6A (RMS)@115VAC, 3A (RMS)@230VAC |
| Inrush Current | 80A max. for 115VAC, 160A max. for 230VAC |
| Output | |
| Voltage | +3.3V/12A,+5V/14A,+12V/25A,-12V/0.3A,+5Vsb/3A |
| Over Voltage Protection | +3.3V: 3.7V-4.5V |
| | +5V: 5.7V-7.0V |
| | +12V1 : 13.3V-16V |
| Short Circuit Protection | +3.3V, +5V, +12V, -12V shutdown and latch off |
| General | |
| Watt | 300 |
| Efficiency | 87% |
| MTBF | 100000 |
| Operating temperature | 0°C ~ 50°C |
| Storage temperature | -40°C ~ 80°C |
| Dimensions | 150 x 81.5 x 40.5 |
| Output Connector | 1 x 20+4-PIN ATX, |
| | 2 x 4-pin 12V CPU, |
| | 1 x HDD/CDROM, |
| | 1 x FDD, |
| | 2 x Graphics card power, |
| | 2 x SATA |

Ordering Information

| | |
|---------------|--|
| ACE-A630C-R11 | 1U flex ATX 300W Power Supply;90~264VAC;ERP;CCL;RoHS |
|---------------|--|