

WS-855GS

15" IP 64 Waterproof Workstation: Robust, Shock Resistance



Features

- » Die-cast aluminum front panel with integrated LCD screen
- » New robust chassis and retention kit structure for shock and vibration
- » Front panel, membrane keys, mouse pad and drive-bay enclosure meet IP 64 standard for tough environment
- » Full function membrane keys and submerged OSD controller
- » Advanced thermal and air-flow design
- » Analog VGA interface supports all CPU boards

Specifications

Dimensions	
Dimensions	483 x 353 x 261
Environment	
Humidity	10%~95%, non-condensing
Operating Temperature	0°C ~ 50°C
Storage Temperature	-10°C ~ 60°C
Function Key	
Function Key	10 Keys
KeyPad	
KeyPad	59 Keys
LCD	
Backlight MTBF	70000 (LED Backlight)
Brightness (cd/m2)	450
Contrast Ratio	800:1
LCD Color	16.2M
Resolution	1024 x 768
Size	15"
Touch	
Touch Screen	5-wire resistive touch screen
Weight	
Weight	12 kg / 18.2 kg

Ordering Information

WS-855GSATX/A130B/R-R40	8U m-ATX 15" 450cd/m ² XGA LCD workstation with ACE-A130B-R10 300W ATX with PFC power supply and 15" resistive touch screen, M-ATX version, RoHS, R40
WS-855GS/A130B/R-R40	8U 15" 450cd/m ² XGA LCD 10-slot industrial workstation with ACE-A130B-R10 300W ATX with PFC power supply and 15" resistive touch screen, RoHS, R40

Packing List	
1 x AC Power Cable	1 x VGA Cable
1 x PS_ON Cable for ATX signal	4 x Press Stick Kit (Long)
3 x Press Stick Kit (Short)	7 x Press Stick Rubber
1 x User Manual	1 x Keypad / MousePad PS/2 Cable (For SBC Models)
1 x Keypad / MousePad PS/2 Cable (For m-ATX (Motherboards) Models)	1 x RS-232 Cable / Touch Pen for Touch Screen