

네트워크 장비 > Network Appliance > ARM-based network appliances

PUZZLE-M902

OpenWrt Network Appliance with Marvell® CN9130 Processor, up to three 10GbE, six 2.5GbE with 4GB eMMC

Features

» Marvell® CN9130 quad-core Armv8 Cortex-A72 @ up to 2200 $\rm MHz$

» Six 2.5GbE RJ-45 ports (two via Marvell CN9130; four via Marvell 88F8215)

» Three 10GbE RJ-45 ports (one via Marvell CN9130; two via Marvell 88F8215)


 $^{\rm w}$ 4 GB eMMC; one console port (pin-header); one reset button

 $\ensuremath{\text{\tiny N}}$ LED indicators: status/power & WAN/LAN interface indicator

Specifications

Form Factor						
Form Factor	Desktop					
System						
СРИ	Marvell® CN9130 quad-core Armv8 Cortex-A72 @ up to 2200 MHz					
Memory	System: 4G					
Cooling method / System Fan 1 system fan						
Physical Characteristics						
Dimensions (LxWxH) (mm) 226 x140 x 50.5						
Storage						
Storage	1 x M.2(NGFF) : 2242/2280 M Key M.2 PCIe Gen. 3 x1					
	1 x eMMC : onboard 4 GB					
I/O Interface						
Ethernet	9 x LAN :					
	2 x 2.5GbE LAN integrated in CPU via PHY Aquantia AQR112R					
	4 x 2.5GbE LAN via Marvell 88F8215 (PHY: Aquantia AQR112R)					
	1 x 10GbE LAN integrated in CPU via PHY Aquantia AQR113					
	2 x 10GbE LAN via Marvell 88F8215 (PHY: Aquantia AQR113)					
I/O Interface 1 x External USB 3.2 Gen1x1						
Environment						
Operating Temperature	0°C ~ 40°C (32°F ~ 104°F)					
Storage Temperature						
Humidity	5~95% non-condensing, wet bulb: 27°C					
Certifications						
Safety & EMC	CE/FCC/BSMI (BSMI safety)/VCCI, LVD					
OS Support						
OS Support	OpenWrt					

Ordering Information





Desktop Network Appliance with Marvell CN9130 Processor ,6 x 2.5GbE and 3 x10 GbE on Board 4GB eMMC & 1x M.2 slot, RoHS.

Packing List

1 x Power cord	1 x Power adapter

Why You Need Software Defined Router?

High Reliability, Performance and Availability







www.ieiworld.com

HIGH SCALABILITY Rich open resource services to achieve any requirement

e SUPER SPEED Design with 2.5GbE and 10GbE ports for faster package transfer FASTER TIME TO MARKET Deploy network applications and services faster by leveraging open software packages

Get Your Office Ready for New Gen. Software Defined Router

The growing number of connected personal and IoT devices has led to an overall increase in network density. The PUZZLE-M902 is IEI's latest product series – Software Defined Router, which is pre-installed with OpenWrt and features high speed and high flexibility to optimize your network performance.

This series is integrated with 2.5GbE and 10GbE ports and the interfaces can be defined with various combination to meet your demands. Moreover, its function can also be expanded by open source applications supported in the OpenWrt community. It is ideally suited for a wide range of applications, such as SOHO and SMB networking infrastructure.



High-end Arm-based Platform with Marvell Quad-core SoC

The Marvell CN9130 is a quad-core Armv8 Cortex-A72 system-on-chip (SoC). The high-performance processor offers a complete function and acceleration for networking and security applications. It can accelerate the packet processing for NAT, QoS and packet filtering, and offload the processor on multiple IPSec/SSL VPN tunneling.






Accelerate NAT, QoS, packet filtering, and offload IPSec/ SSL VPN tunneling

High computing with

quad-core SoC

Flexible High-speed Network Deployment

The Marvell CN9130 is a quad-core Armv8 Cortex-A72 system-on-chip (SoC). The high-performance processor offers a complete function and acceleration for networking and security applications. It can accelerate the packet processing for NAT, QoS and packet filtering, and offload the processor on multiple IPSec/SSL VPN tunneling.



Built stability for multi-device connections

6 x 2.5 GbE 3 x 10 GbE

Super speed for package transfer

Customize Your Network with OpenWrt

The hottest open source project, OpenWrt, which is based on Linux-based embedded operating system and used on embedded devices to route network traffic. It uses the command line interface (ash shell) or the web interface (LuCI) to configure OpenWrt. Approximately 3,500 optional software packages can be installed through the opkg package management system. It provides detailed possibilities to configure common network-related functions, such as IPv4, IPv6, DNS, DHCP, VPN, shadowsocks, DLNA, routing, Dynamic DNS, firewall, NAT, port forwarding, file sharing via SAMBA, NFS, FTP, SFTP and MQ Telemetry Transport through Mosquitto.



The hottest open source project for router

Simple and Visible Network Operation

Powered by OpenWrt, the PUZZLE-M902 provides a userfriendly web interface, a clear dashboard and port indicators to help you handle daily network management tasks. Users can not only efficiently manage all connected wires through OpenWrt OS in real time, but also configure firewall, VPN, security and advanced network functions.



Various software packages you can have

perrWitt Status - System - Services	Network + VPN + Logost	1059-1040
tatus		
stem		
lostname	OperWit	
ladel	Public-MID1	
achilecture	Marvel Cortex-A72 jaarch04	
innware Newton	OperAVE21.01-INVPDHOF (18036-03811 IEARS (LuC) speever-21.02 (see of girl)1.124.3803 9403180	
Servel Tertstan	6.4.114	
osai Time	2021-05-20 10:02:09	
lçalanıw	208 32hri 24	
card Avenage	0.06.0.00, 0.00	
emory		
iotal Analhabhe	2 HH (18.1 3 HH (18. (91.4))	
hard	152.14 M9 / 3.06 Q8-0%	
Lufferind	1.08 HBI / 3.86 EBI (2%)	
lached	16.04 MB / 0.06 GB (2%)	
etwork.		

Make Security Configuration Easier than Ever



There are multiple packages available in the OpenWrt package repository and designed with clear user interface to support IT developer for installing and deploying the security function of network. OpenVPN, a virtual private network (VPN), and Firewall3 (fw3) which uses netfilter/iptable rule builder for firewall applications, are two of the most popular packages for creating high reliable network security.

OpenVPN Instance		and their current of	1940					
Harm	Enabled	Barted	Start/Step	Part	Protocol			
custom_config	0	~	start			Ect Delete		
sample_server		- 14	stat	1.004	udp	Fat Debte		
sample_client			- test		salp.	Reis Databa		
Template based cor	Aguration	3 months	npane			* A83		
OVPN configuration	file upload							
indense name		##UX	建排程 案 共适于生计程序					

OpenV	kt maa	a-tysten-t	lontost	- 1604	ux -	1991 - L	ogant	(<u>60</u>
	all Sta							Hide empty chains Please Cos	rises PestatiProval
Table: I Chain N		Cy: ACCEPT, 0 Per	okarta, G	a Tufa	9				
Pics.	Tuffe	Target	Prot	in .	0st	Source	Destination	Options	Conment
78	5.00 HB	ACCEPT		8		103.69	04.030		
186.8	487.55 (3)	input_cole	1			£03.6/8	01030		Custom input rule chain
5.12 K	141.23 KB	ACCEPT		•		6.03.6/8	08.030	datase RELATED, EXTRACTORE	
18	840 B	eyn_foed	Np			LO3.6/8	0.8.0.3/0	top flage dx11/bx08	
287	14.57 KB	acce_las_input.	4	in in		£03.6/3	06030		
022	541.75 HB	2004_440_0245		980		6.03.69	08.036		
Chain P	ORWARD	Policy: DROP, 0 P	Packata	.0 B To	fic)				
Picto.	Table	Terpet	Prot.	in	Out	Gourse	Destination	Options	Gomment
5.30 K	2.88 MR	foreacting_cole	48	-	•	03.035	603.09		Cultarn towarding rule chain
5.25 K	2.85 MB	ADDEPT	**			0.8.000	60.809	ctitatia RELATED.RETWOLISHED	
126	allor HB	crea.ion.iceward	**	brian		0.8.0.040	60.8.09		
	0.8	care, ear, bread		(and		01000	00109		

Connection Configuration



Dimensions (Unit: mm)

