

# IOVU-572M

5.7" TFT VGA LCD with resistive touchscreen



## Features

- » 5.7" TFT VGA LCD with resistive touchscreen
- » XScale® PXA310 624MHz CPU
- » Powered by Windows® CE 6.0
- » Built-in Ethernet LAN and Wi-Fi
- » Built-in RS-232/422/485 Port
- » Support .Net Frame Work V3.5

## Specifications

<b>Environment</b>	
Humidity	5%-90% RH
Operating Temperature	-10°C~ 60°C
<b>LCD</b>	
Brightness (cd/m2)	400
Resolution	VGA
Size	5.7"
Viewing Angle (H-V)	140° / 100°
<b>Physical Characteristics</b>	
Dimensions (LxWxH) (mm)	180 x 135 x 46
Net Weight	0.7 Kg
<b>Power</b>	
Power adapter	12~36V DC input
Power consumption	Max. 14W
<b>System</b>	
CPU	XScale® PXA310 624 MHz
Memory Ext.	256 MB DDR2
On-board Memory	128 MB
<b>Touch</b>	
Touch Screen	Resistive Type
<b>I/O Interface</b>	
I/O Interface	1 x Power In(terminal block DC input)
	1 x RS-422/485
	1 x SD Slot
	2 x Speaker(1.5W)
	2 x USB 1.1
	2 x LAN(10/100)
	1 x WIFI(802.11a/b/g/n)
	1 x Power Switch(AT mode)

## Ordering Information

IOVU-572M-CE6/WOWL/-R11	RISC PANEL PC, 5.7" LCD,Marvell PXA310 624MHZ ,NO WIFI,WIN CE6.0,RoHS
IOVU-572M-CE6/-R12	RISC PANEL PC, 5.7" LCD,Marvell PXA310-B1 624MHZ, BUILT-IN WIFI,WIN CE6.0,RoHS