

## LCD-KIT-F15A

15" Slim Open Frame Monitor



### Features

- » 12.1"~19" open frame architecture for embedded integration
- » Over 350cd/m<sup>2</sup> high brightness and 50000hrs MTBF long lifetime panel
- » Analog VGA or digital DVI interfaces support most of general systems
- » Various touch panel solution : Resistive / Resistive touch windows / PCAP multi-touch
- » Optional 9-36V DC module
- » -20°C~60°C extended operating temperature
- » Support software OSD for remote control applications

### Specifications

Dimensions	
Dimensions	380.1 x 304.6 x 43.2
Environment	
Humidity	10%~95%, non-condensing
Operating Temperature	-20°C ~ 60°C
Storage Temperature	-20°C ~ 70°C
LCD	
Brightness (cd/m <sup>2</sup> )	450
Contrast Ratio	800:1
LCD Color	16.2M
Resolution	1024 x 768
Size	15"
Viewing Angle (H-V)	160°/150°
Touch	
Touch Screen	Resistive type 5-wire single touch / Penmount 6000 or Projected capacitive 2-point touch / EETI EXC7200 (Assembly by adhesive tape)
Weight	
Weight	2.6 kg/3.1 kg

### Ordering Information

LCD-KIT-F15A-R10	15" 450 cd/m <sup>2</sup> XGA open frame monitor, VGA and DVI-D input, R10
LCD-KIT-F15A/R-R10	15" 450 cd/m <sup>2</sup> XGA open frame monitor, VGA and DVI-D input, Resistive touch screen RS-232/USB interface,R10
LCD-KIT-F15A/TW-R10	15" 450 cd/m <sup>2</sup> XGA open frame monitor, VGA and DVI-D input, Resistive touch window RS-232/USB interface,R10
LCD-KIT-F15A/PC-R10	15" 450 cd/m <sup>2</sup> XGA open frame monitor, VGA and DVI-D input, Projected capacitive touch window USB interface,R10

### Packing List

1 x AC power cable	1 x VGA cable
--------------------	---------------

1 x USB cable (for Touch)	1 x AC power adapter
---------------------------	----------------------