

ICT-2000 AS

CFast Series SLC



Features

CFast Series SLC

Specifications

| | |
|-----------------------------------|-------------------|
| ATA Security | |
| ATA Security | Yes |
| Capacity (GB) | |
| Capacity (GB) | 2GB-64GB |
| DC Power Input | |
| DC Power Input | 3.3V |
| Dimensions | |
| Dimensions | 42.8 x 36.4 x 3.6 |
| Flash Type | |
| Flash Type | SLC |
| IDE Transfer Mode | |
| IDE Transfer Mode | Yes |
| Max. Power Consumption | |
| ConsumptionMax. Power Consumption | 390mA |
| P/N | |
| STD(0°C~+70°C) | ICT-2000IA-2GB |
| | ICT-2000IA-4GB |
| | ICT-2000IA-8GB |
| | ICT-2000IA-16GB |
| | ICT-2000IA-32GB |
| | ICT-2000IA-64GB |
| WT(-40°C~+85°C) | ICT-2000WA-2GB |
| | ICT-2000WA-4GB |
| | ICT-2000WA-8GB |
| | ICT-2000WA-16GB |
| | ICT-2000WA-32GB |
| | ICT-2000WA-64GB |
| S.M.A.R.T | |
| S.M.A.R.T | Yes |
| Sequential R/W | |
| Sequential R/W | 285/260 MB/sec |
| Environment | |

| | |
|-----------------------|---|
| Operating Temperature | 0°C~+70°C (Standard)/-40°C~+85°C (Industrial) |
| Operating Vibration | Vibration: 15 (G), 10~2000 (Hz) |
| Operating Shock | 1,500 G, 0.5 ms |
| Storage Temperature | -40°C~+100°C |

Ordering Information

| | |
|-----------------|---|
| ICT-2000IA-2GB | Flash Disk; Sata Interface CompactFlash, Standard, SLC, 0°C~70°C, R:80MB/s W:55MB/s, 2GB |
| ICT-2000IA-8GB | Flash Disk; Sata Interface CompactFlash, Standard, SLC, 0°C~70°C, R:80MB/s W:75MB/s, 8GB |
| ICT-2000IA-16GB | Flash Disk; Sata Interface CompactFlash, Standard, SLC, 0°C~70°C, R:80MB/s W:75MB/s, 16GB |
| ICT-2000IA-64GB | Flash Disk; Sata Interface CompactFlash, Standard, SLC, 0°C~70°C, R:285MB/s W:260MB/s, 64GB |
| ICT-2000WA-2GB | Flash Disk; Sata Interface CompactFlash, Standard, SLC, -40°C~85°C, R:80MB/s W:55MB/s, 2GB |
| ICT-2000WA-32GB | Flash Disk; Sata Interface CompactFlash, Standard, SLC, -40°C~85°C, R:285MB/s W:260MB/s, 32GB |
| ICT-2000WA-16GB | Flash Disk; Sata Interface CompactFlash, Standard, SLC, -40°C~85°C, R:80MB/s W:75MB/s, 16GB |
| ICT-2000WA-64GB | Flash Disk; Sata Interface CompactFlash, Standard, SLC, -40°C~85°C, R:285MB/s W:260MB/s, 64GB |
| ICT-2000IA-4GB | Flash Disk; Sata Interface CompactFlash, Standard, SLC, 0°C~70°C, R:80MB/s W:55MB/s, 4GB |
| ICT-2000IA-32GB | Flash Disk; Sata Interface CompactFlash, Standard, SLC, 0°C~70°C, R:285MB/s W:260MB/s, 32GB |
| ICT-2000WA-4GB | Flash Disk; Sata Interface CompactFlash, Standard, SLC, -40°C~85°C, R:80MB/s W:55MB/s, 4GB |
| ICT-2000WA-8GB | Flash Disk; Sata Interface CompactFlash, Standard, SLC, -40°C~85°C, R:80MB/s W:75MB/s, 8GB |