

# DRPC-242-ADL-P

Fanless DIN-Rail Embedded System



## Features

» Supported CPUs:

Intel® Core™ i7-1370PE (up to 4.8GHz, 14-core, 28W TDP)

Intel® Core™ i7-1260P (up to 4.7GHz, 12-core, 28W TDP)

Intel® Core™ i5-1340PE (up to 4.5GHz, 12-core, 28W TDP)

» 2 x USB 3.2 Gen2 & 4 x USB 2.0

» 2 x RS-232 & 2 x RS-422/485 (with 2.5KV isolation)

» CE/FCC compliant

## Specifications

| Form factor     |  |
|-----------------|--|
| SBC Form Factor | » Supported CPU:   |
|                 | Intel® Core™ i7-1370PE (up to 4.8GHz, 14-core, 28W TDP)            |
|                 | Intel® Core™ i7-1260P (up to 4.7GHz, 12-core, 28W TDP)             |
|                 | Intel® Core™ i5-1340PE (up to 4.5GHz, 12-core, 28W TDP)            |
|                 | » Chipset:   |
|                 | SoC  |
|                 | » System Memory:   |
|                 | 2 x SO-DIMM slot DDR4 3200 MHz (8 GB pre-installed) (up to 64GB)   |
|                 | » Power:   |
|                 | 3-pin terminal block: 12 ~ 28 VDC                                  |
|                 | Consumption: 12V@4.46A (Intel® Core™ i7-1260P with DDR4 8G Memory) |
| 輸出/入介面          |  |
| I/O Ports       | » USB:   |
|                 | 2 x USB 3.2 Gen2   |
|                 | 4 x USB 2.0  |
|                 | » Ethernet:  |
|                 | 1 x 2.5 GbE by Intel® I226LM controller support iAMT               |
|                 | 2 x 2.5 GbE by Intel® I226-V controller                            |
|                 | » Display:   |
|                 | 1 x lockable HDMI™ 1.4b (up to 4096 x 2160@30Hz)                   |
|                 | 1 x DP 1.4b (up to 4096 x 2160 @60Hz)                              |
|                 | » COM Port:  |
|                 | 2 x RS-232 (DB9 with 2.5KV isolation)                              |
|                 | 2 x RS-232 (optional)  |
|                 | 2 x RS-422/485 with AFC (DB9 with 2.5KV isolation)                 |
|                 | » GPIO:  |
|                 | 1 x 12-bit(6-in, 6-out)(optional)                                  |
|                 | » TPM:   |

|                                 |   |
|---------------------------------|---|
|                                 | Support Intel PTT                                       |
|                                 | » Watchdog Timer:                                       |
|                                 | Programmable 1 ~ 255 sec/min                            |
| <b>擴充槽</b>                      |   |
| 擴充槽                             | » M.2:  |
|                                 | 1 x 2230 A-key (PCIe Gen3 x1/USB 2.0) Support Vpro      |
|                                 | 1 x 3042/52 B-key (PCIe Gen3 x1/USB 3.2 Gen2/USB 2.0)   |
|                                 | 1 x On-board SIM card socket (hinge type) for M.2 B key |
|                                 | 1 x 2280 M-key (PCIe Gen4 x4)                           |
|                                 | » Backplane:  |
|                                 | 1 x PCIe Gen3 x4 (optional)                             |
| <b>系統</b>                       |   |
| 冷卻方式/系統風扇                       | Fanless   |
|                                 | 4-pin external system fan connector                     |
| Drive Bays                      | 1 x 2.5" SATA 6Gb/s SSD bay                             |
| <b>指示燈與按鈕</b>                   |   |
| 按鈕                              | 1 x Power button  |
|                                 | 1 x 2-pin terminal block for Remote Power Button,       |
|                                 | 1 x Reset button  |
|                                 | 1 x AT/ATX switch,                                      |
| 指示燈                             | 1 x Power LED   |
|                                 | 1 x HDD LED   |
| <b>Physical Characteristics</b> |   |
| Construction                    | Extruded aluminum alloy                                 |
| <b>Color</b>                    |   |
| Color                           | Black   |
| <b>Dimensions</b>               |   |
| Dimensions                      | 81 x 150 x190 mm  |
| <b>Weight</b>                   |   |
| Weight                          | 1.88 / 2.66KG   |
| <b>Environment</b>              |   |
| Operating Temperature           | -20°C ~ 60°C with 0.7M/S air flow (SSD)                 |
| Humidity                        | 10% ~ 95% non-condensing                                |
| Operating Vibration             | 10-500 Hz, 1.04 Grms, random, 1 hr/axis (SSD)           |
| Operating Shock                 | Half-sine wave shock 5G, 11ms, 3 shocks per axis (SSD)  |
| Safety & EMC                    | CE, FCC, UKCA   |
| <b>OS Compatible</b>            |   |
| OS Compatible                   | Microsoft® Windows® 10/11, Linux                        |

## Ordering Information

|                           |  |
|---------------------------|--|
| DRPC-242-ADL-P-Ri7ECS-R11 | Embedded system with 13th Gen Intel® Core™ i7-1370PE, TDP 28W, 8GB DDR4 pre-installed memory, HDMI/DP, 3 x 2.5GbE LAN, 4 x COM, 6 x USB, 12~28V DC, RoHS |
| DRPC-242-ADL-P-Ri5ECS-R11 | Embedded system with 13th Gen Intel® Core™ i5-1340PE, TDP 28W, 8GB DDR4 pre-installed memory, HDMI/DP, 3 x 2.5GbE LAN, 4 x COM, 6 x USB, 12~28V DC, RoHS |
| DRPC-242-ADL-P-Ri3ECS-R11 | Embedded system with 13th Gen Intel® Core™ i3-1320PE, TDP 28W, 8GB DDR4 pre-installed memory, HDMI/DP, 3 x 2.5GbE LAN, 4 x COM, 6 x USB, 12~28V DC, RoHS |

## Packing List

|                           |                |
|---------------------------|----------------|
| 1 x DIN-rail mounting kit | 1 x Screw pack |
| 1 x Terminal block        |                |